

Product Information

Mipa 2K-Härter H10 is a multi-purpose, UV-resistant hardener based on isocyanate for Mipa 2K-paints, 2K-primers, 2K-fillers, 2K-clearcoats, etc.

Colour shade	colourless		
Mixing ratio	see the base product		
Storage	about 9 months in the original tins		
Thinner	Mipa 2K-Verdünnung		
Spraying viscosity 20°C	approx. 18 s 4 mm DIN 53 211		
Application	spraying pressure	spraying nozzle	spraying operations
Air / Flowjar - Spray gun			
Airless / Airmix			
Pot life	see the base product		
Coat thickness / dry film			
Curing time / Flash off time			
Drying (with Mipa PUR-Lack)	recoat time	dust dry	Set to touch
Object temp. 20°C			
Object temp. 60°C			

Remarks:

Stir well with the base product before use.
 Mipa 2K-Hardener H 10 reacts with humidity, therefore close tin immediately after use.
 Avoid inhalation of spraying mist.

Marking	VbF	Hazardous materials ordinance
Mipa 2K-Härter H10	A II	inflammable, Xi irritant; Contains aliphatic polyisocyanate

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your Environment!

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.